



Presentation:

Gazette



Image:

Small

Français



1 of 1

View Images

(21) Int. PCT/CH00/00017
Application
Number:

(22) Int. 11 January 2000
Filing Date: (11.01.2000)

(30) Priority Data

199 00 792.6 12 January DE
1999
(12.01.1999)

(71) Applicant:

**DISETRONIC
LICENSING AG**
Brunnmattstrasse 6,
CH-3401 Burgdorf ; (CH).
[CH/CH]. *(for all
designated states except US)*

(72) Inventors; and**(75) Inventors/Applicants:**

KIRCHHOFFER, Fritz
Wassermatt, CH-3454
Sumiswald ; (CH) [CH/CH].
GURTNER, Thomas
Haperigweg 6, CH-3425
Koppigen ; (CH) [CH/CH].

(81) Designated States:

AE, AL, AM, AT, AU, AZ,
BA, BB, BG, BR, BY, CA,
CH, CN, CU, CZ, DE, DK,
EE, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL,
IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT,
LU, LV, MD, MG, MK,
MN, MW, MX, NO, NZ,
PL, PT, RO, RU, SD, SE,
SG, SI, SK, SL, TJ, TM,
TR, TT, UA, UG, US, UZ,
VN, YU, ZA, ZW ; ARIPO
patent (GH, GM, KE, LS,
MW, SD, SL, SZ, TZ, UG.

(51) International
Patent
Classification⁷:
A61M 5/315

A1

(11) Int. WO
Publication
Number: 00/41753

(43) Int. 20 July 2000
Publication
Date: (20.07.2000)

(54) Title:DEVICE FOR ADMINISTERING AN
INJECTABLE PRODUCT

(57) Abstract

The invention relates to a device for administering a dose, comprising a housing with a reservoir, a piston that pushes out the product from the reservoir when its is displaced towards an outlet of said reservoir in the advance direction, a drive member (6), a driven member that is entrained by the drive member (6) when said drive member (6) is displaced in the advance direction and that pushes the piston in the advance direction and a dosing member (15) that can be rotated around the displacement axis (V) of the drive member (6) to regulate the administration of a dose of the product to be delivered. The drive member (6) and the dosing member (15) come to rest with at least one stop (14, 18), one of which is embodied on the drive member (6) and the other one is configured on the dosing member (15). At least one of said stops (14, 18) runs at least spirally around the displacement axis (V) of the drive member (6). The at least one spiral stop (18) has a progression with a constant slope (&agr;).

